

FF-3DP-ABS1.75-02-Y

ABS Yellow, 1.75 mm, 0.6 kg

VERSATILE & EASY TO USE

- Acrylonitrile butadiene styrene (ABS) is a common thermoplastic strong and durable plastic available in a range of colors.
- ABS is the plastic used in lots of things around us and is perfect for heated plastic extrusion 3D printing.



Specifications

Material: ABS, 1.75 mm diameter

Weight: 0.6 kg/spool Density at 215°C: 1.05 g/cm3

Melt Flow Index at g/10min, 220°C/5kg: 1.8

Melt Point: 210 250 °C

Heat-Deflection-Temperature at 0.455 MPa: 85 100 °C

Yield Strength at 5mm/min: 45 MPa

Impact Strength: 18 KJ/m2 Ensile Break: 25 % Diameter: 1.75 ± 0.05 mm

Spool dimensions: 160mm diameter x 53mm height x 32mm central hole

Features

- ABS filament with 1.75 mm diameter
- Excellent chemical resistance
- High Stiffness and good impact resistance at low temperatures
- Easily processed with good surface finish
- Can be used in a variety of 3D printers
- 0.6 kg spool

Packaging

Q'ty in crtn, pcs 12 Crtn volume, CUM 0.032 Crtn weight, kgs 10.26 Individual package size LxWxH: 175x175x70 mm Carton size LxWxH: 360x370x240 mm Country of origin CN Barcode 8716309091626 Customs code 3916909000

System requirements

A 3D printer with 1.75 mm extruder of temperature around 230 $^{\circ}\text{C}$, suitable for ABS filament

Certificates





